

GALVANISED IRON PRIMER

Surface Preparation	<ul style="list-style-type: none"> • Ensure that surfaces are dry, sound, and free from dust, dirt, grease and oil before painting. <ol style="list-style-type: none"> 1. GALVANISED STEEL (new and weathered): Remove all traces of temporary protective coating, dirt, grease, etc. from new surfaces using GALVANISED IRON CLEANER (GIC 1). Remove all traces of the cleaner by rinsing with fresh water. Check surface for water break-free condition (i.e. water completely wets the surface without crawling back into droplets). If necessary, repeat the cleaning process until this condition is obtained. Allow surface to dry and apply the PRIMER the same day. Prepare weathered surfaces as above to obtain a clean surface free from oxidation. Remove red and white rust by abrading back to bare metal. Spot prime areas where red rust has been removed with COASTCOTE ETCH PRIMER RED OXIDE (SNK 2) – see Product Data Sheet for application details. 2. PREVIOUSLY PAINTED SURFACES: Remove loose and flaking paint and rust and clean bare metal areas as in 1. above before spot priming bare metal areas with GALVANISED IRON PRIMER (GIP 1).
Application	<ul style="list-style-type: none"> • Apply by brush or roller. It can be sprayed using airless spraying equipment without thinning. However, if dilution is necessary, use a minimum amount of WATER only.
Cautions	<ul style="list-style-type: none"> • DO NOT mix with other galvanised iron primers. • Do not overcoat with two-pack polyurethanes, epoxies and cellulose nitrate paints. • Observe overcoating times.- • Avoid painting during inclement weather or if temperature is below 5 °C.
Safety Precautions	<ul style="list-style-type: none"> • Keep out of reach of children. • Ensure good ventilation during application and drying. • In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention. • Refer to Material Safety Data Sheet for complete information.
Transportation	<ul style="list-style-type: none"> • This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996).

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 534-6151
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

MOGALE CITY

(KRUGERSDORP):

Private Bag X4010
Kenmare 1745
Tel: (011) 951-4500
Fax: (011) 955-4136

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 434-606