



## PROFESSIONAL PLASCOTEX TEXTURED ACRYLIC

**PRODUCT DATA SHEET NO.:** L-25-G  
**DATE:** OCTOBER 2004

**PRODUCT CODE:** PTX 900

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

**Product Description** A flexible heavy duty waterbased textured coating for use on walls and ceilings for interior and exterior use.

**Intended Uses**

- Specially formulated as a decorative finish for use on off-shutter concrete, fibre-cement, etc. eliminating the necessity to plaster.
- General textured finish for smooth cement plastered walls.

**Features**

- **PLASCOTEX** has excellent filling properties and is therefore ideal for covering blow holes and imperfections.
- Highly decorative texture finish. Can be varied from smooth stipple to a sharper pointed stipple.
- May be overcoated with **WATERBASED GLAZE COAT GLOSS (REF 1124)** or **MATT (REF 1125)** on interior and exterior surfaces or solvent based **GLAZE COAT (CV 82)**
- on interior surfaces to improve resistance to dirt pick-up.
- May be overcoated with emulsion paints if specific colours are required, e.g. **WALL & ALL (WAA)**, **DOUBLE VELVET (VEL)** or **POLVIN (EPL)**.

<b>Product Information</b>	Appearance	Matt stipple textured finish
	Colour	White
	Generic type	Modified acrylic emulsion
	Solids	Approx. 80 % by mass; 67 % by volume
	Recommended DFT	Min.: 1 mm      Max.: 2 mm
	Theoretical spreading rate	1.3 m <sup>2</sup> /ℓ at 500µm DFT
	Practical spreading rate	Please apply appropriate correction factors.
	Viscosity at 23 °C	Approx. 105 KU (thixotropic)
	S G at 23 °C	1,62 kg / ℓ (typical)
	Flash point	> 65°C

<b>Application Details</b>	Mixing	Stir thoroughly with a flat paddle until homogeneous.	
	Method	Texture roller or propile roller if a lower texture is required.	
	Thinning	<b>Water</b> - not normally required. Thin with minimum amount if necessary.	
	Cleaning	Water	
	Substrate	Thoroughly cleaned, primed concrete and plaster.	
	Application Environment	Surface Temperature	
		Ambient Temperature	
		Relative Humidity	
		Min.: 5 °C      Min.: 5 °C      -	
		or 2 °C min. above dew point	
		Max.: 40 °C      Max.: 40 °C      Max.: 85 %	
	Drying time	Touch dry	4 h at 23 °C
		Recoating	16 h at 23 °C
		Dry to handle	16 h at 23 °C
		Hard dry	48 h at 23 °C

**Storage and Packaging** Store away from direct sun, heat and severe cold.  
Packaging: 20ℓ.

**Transportation** This product is non-classifiable in accordance with Transportation and Classification of Dangerous Goods Act (1996).

## PROFESSIONAL PLASCOTEX TEXTURED ACRYLIC

---

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>• Ensure that surfaces are dry, sound, and free from dust, dirt, grease and oil before painting.</li> </ul> <ol style="list-style-type: none"> <li>1. <b>OFF-SHUTTER CONCRETE, PRECAST CONCRETE PANELS AND ONE-COAT CEMENT PLASTER:</b>                      Ensure that surfaces have dried for at least 4 weeks before coating. Remove shutter release agents with <b>AQUASOLV DEGREASER (GR 1)</b> and rinse thoroughly with water. Prepare then stop with <b>POLYCELL MENDALL 90 ALL PURPOSE ADHESIVE FILLER</b> or <b>POLYCELL POLYFILLA EXTERIOR CRACK FILLER</b> and allow to dry.                     <ol style="list-style-type: none"> <li>1.1 Apply <b>PROFESSIONAL PLASTER PRIMER (PP 700)</b>.</li> </ol> </li> <li>2. <b>NEW HARDWALL GYPSUM PLASTER:</b>                      Apply one coat of <b>PROFESSIONAL PLASTER PRIMER (PP 700)</b>.</li> </ol>
<b>Application</b>	<ul style="list-style-type: none"> <li>• Apply two full coats of <b>PLASCOTEX</b> to achieve desire texture and finish.</li> <li>• Allow at least 48 hours to dry before applying a <b>GLAZE COAT (e.g. CV 82, REF 1124 or REF 1125)</b> if required.</li> </ul>
<b>Cautions</b>	<ul style="list-style-type: none"> <li>• Avoid painting during inclement weather or if temperature is below 5 °C.</li> </ul>
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>• Keep out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.</li> <li>• Refer to Material Safety Data Sheet for complete information.</li> </ul>

---

**DISCLAIMER:**

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**N.B.:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER: Quote product name, product code number, packaging and colour.**

**BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED**

**CAPE TOWN:**

P O Box 42  
 Eppindust 7475  
 Tel: (021) 505-2400  
 Fax: (021) 534-3791

**DURBAN:**

Private Bag X16  
 Mobeni 4060  
 Tel: (031) 451-3200  
 Fax: (031) 451-3411

**MOGALE CITY**

**(KRUGERSDORP):**  
 Private Bag X4010  
 Kenmare 1745  
 Tel: (011) 951-4500  
 Fax: (011) 955-4136

**PORT ELIZABETH:**

P O Box 1594  
 Port Elizabeth 6000  
 Tel: (041) 401-1400  
 Fax: (041) 434-606