



A member of the **FREEWORLD** COATINGS GROUP

## PEARLESCENT EFFECT PAINT

TECHNICAL DATA SHEET NO.: **L-154-A**  
DATE: **OCTOBER 2008**

### PRODUCT CODE: **DRP**

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

<b>Product Description</b>	A premium water based finish that captures the essence of natural pearl. It is suitable for interior use.		
<b>Intended Uses</b>	<ul style="list-style-type: none"><li>Used for trim work - to provide fashionable pearlescent effect.</li><li>Can be used on walls and suitably prepared wood and metal substrates.</li></ul>		
<b>Product Information</b>	Appearance	Pearlescent	
	Colour	DRP 1 – TURQUISE DRP 2 – GOLD DRP 3 - WHITE	
	Solids	+/- 40% v/v	
	S G at 23 °C	1.203	
	Recommended DFT	Varies with the effect to be created	
	Mixing ratio	<b>READY TO USE, MIX WELL</b>	
<b>Application Details</b>	Method	Brush or Roller	
	Thinning	Not recommended	
	Cleaning	Water	
	Substrate	Well prepared, primed and undercoated surfaces.	
	Application Environment	Surface Temperature	Ambient Temperature
		Min.: 5 °C	Min.: 10 °C
		or 2 °C min above dew point	
		Max.: 40 °C	Max.: 40 °C
			Max.: 85 %
	Drying time	Touch dry	60 min at 23 °C - 35 microns DFT
		Recoating	8h
		Dry to handle	8 h at 23 °C
<b>Storage and Packaging</b>	Store away from direct sun, heat and severe cold. Packaging: 1l and 5l plastic containers.		
<b>Transportation</b>	This product is non-classifiable in accordance with Transportation and Classification of Dangerous Goods Act (1996).		

**PEARLESCENT EFFECT PAINT**

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>Ensure that all surfaces are clean, dry, free from dirt, oil, grease and any contaminants.</li> </ul> <p><b>NEW SURFACES</b>  <b>Cement Plaster, Gypsum Plaster (e.g. Rhinolite or Cretestone):</b></p> <ul style="list-style-type: none"> <li>Apply one coat <b>PLASCON PLASTER PRIMER (UC 56)</b>.</li> <li>Apply one or more coats of <b>PLASCON DOUBLE VELVET, PLAS CON CASHMERE or PLASCON POLVIN</b> in the required colour to achieve a solid base coat colour. Allow to dry thoroughly.</li> </ul> <p><b>PREVIOUSLY PAINTED SURFACES IN GOOD CONDITION</b> (No flaking or peeling paint.)</p> <ul style="list-style-type: none"> <li>Clean down thoroughly with <b>POLYCELL SUGAR SOAP</b> as directed. Rinse to remove all traces of the soap solution. Sand glossy surfaces. Apply one or more coats of <b>DOUBLE VELVET, POLVIN or CASHMERE</b> in the required colour to achieve a solid base coat colour. Allow to dry thoroughly.</li> <li>All <b>other surfaces</b> must be suitably prepared - Refer to Plascon Technical Services Department.</li> </ul>
<b>Mixing</b>	<ul style="list-style-type: none"> <li><b>Ready for use. Thinning is not recommended.</b></li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li><b>Stir well for 5 minutes with a flat paddle before use. During painting stir every 30 minutes.</b></li> <li>Apply one to two coats for desired effect to be evident.</li> <li><b>Apply thin, even coats.</b></li> <li>Avoid over spreading.</li> <li>When brushing, strokes should be in a single direction – vertical, diagonal and horizontal strokes each appear as different shades.</li> <li>Avoid large touch up areas on broadwall application</li> <li>Hamilton’s Poly-Pile or Woolpro rollers and Perfection or Professional brushes are recommended.</li> </ul>
<b>Cautions</b>	<ul style="list-style-type: none"> <li>We recommend familiarising yourself with the effect on a small test area before starting work.</li> <li>All "tools" used to pattern the surface should be cleaned regularly to avoid build-up of material.</li> </ul>
<b>Safety Precautions</b>	<ul style="list-style-type: none"> <li>Non-flammable. No special hazards - apply normal precautions during use.</li> <li>In case of contact with eyes, rinse immediately with water.</li> <li>Keep out of reach of children.</li> <li>Refer to Material Safety Data Sheet for complete information.</li> </ul>

**DISCLAIMER:**

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**N.B.:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER: Quote product name, product code number, packaging and colour.**

**PLASCON SOUTH AFRICA (PTY) LIMITED**

**CAPE TOWN:**

P O Box 42  
 Eppindust 7475  
 Tel: (021) 534-6151  
 Fax: (021) 534-3791

**DURBAN:**

Private Bag X16  
 Mobeni 4060  
 Tel: (031) 451-3200  
 Fax: (031) 451-3411

**MOGALE CITY**

**(KRUGERSDORP):**  
 Private Bag X4010  
 Kenmare 1745  
 Tel: (011) 951-4500  
 Fax: (011) 955-4136

**PORT ELIZABETH:**

P O Box 1594  
 Port Elizabeth 6000  
 Tel: (041) 401-1400  
 Fax: (041) 434-606