



REMOVALL GRAFFITI & GUNK REMOVER

PRODUCT CODE: RCG 400

TECHNICAL DATA SHEET NO: D-7-C

DATE: FEBRUARY 2011

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product Description	Cleaning agent engineered to clean up problem graffiti and overspray without damaging the underlying paint.	
Intended Uses	<ul style="list-style-type: none">• Ideal for removing paint overspray, grease, wax, lipstick, crayon, tape residue, felt markers and pen inks on a variety of surfaces.	
Features & Benefits	<ul style="list-style-type: none">• Fully biodegradable• Contains no methylene chloride• Low odour• Easy clean-up with running water• Non-ozone depleting• Will not fog or streak Perspex or glass• Will not damage most underlying protective paint• Will not burn skin on contact	
Product Information	Appearance	Clear liquid
	Colours	Colourless
	Flash Point	86.5 °C
	Boiling Point	184.6 °C
	pH	8 - 9
	VOC Content	882 g/l
	Density	0.99 g/ml
	Viscosity	14 Seconds (Ford 4 Cup)
	Shelf Life	24 months
Application Details	Mixing	The product should not be diluted and does not need any mixing before application.
	Method	Spray or brush application. Use a small hand pump; weed sprayer or conventional spray equipment capable of producing a fine atomised spray. For small areas, a 500ml spray bottle will be sufficient to apply the product.
	Substrate	Any uncoated or coated surfaces.
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: 500 ml, 3 l and 20 l	



REMOVALL GRAFFITI & GUNK REMOVER

PRODUCT CODE: RCG 400

TECHNICAL DATA SHEET NO: D-7-C

Application	<ul style="list-style-type: none">• Apply an even layer of REMOVALL GRAFFITI & GUNK REMOVER onto the coating being removed.• If using an airless sprayer, always start the sprayer pump at the lowest pressure setting and slowly build up the pressure until an adequate fan pattern has been generated to prevent overspray.• The time required to remove or soften overspray depends on the type of paint, number of layers of paint and the temperature of the substrate. Most overspray will soften within 2 minutes. Do not let overspray stay on for more than 15 minutes. If the work has not been completed, wipe off the softened graffiti/overspray with a cotton cloth and re-apply.• Wipe residue off with a dry cloth, followed by a warm or soapy water rinse.
Safety Precautions	<ul style="list-style-type: none">• Always keep remover out of reach of children.• Ensure good ventilation during application.• Wear protective gloves and goggles while applying.• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.• Harmful if swallowed. Seek medical attention and do not induce vomiting.• Store in a cool dry place away from heat and sparks.• Refer to Material Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P. O. Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

GAUTENG:

P.O. Box 4010
Luipaardsvlei 1743
Tel: (011) 951-4500
Fax: (011) 955-2841

PORT ELIZABETH:

P. O. Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4606