



# REMOVAL GREASE & GRIME REMOVER

PRODUCT CODE: RCS 60

TECHNICAL DATA SHEET NO: D-8-C

DATE: FEBRUARY 2011

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

<b>Product Description</b>	A Water -based concentrate for cleaning and degreasing.													
<b>Intended Uses</b>	<ul style="list-style-type: none"><li>• Ideal for general purpose cleaning such as shop walls, lockers and stove tops.</li><li>• Cleans equipment such as tools, lawn mowers, fireplaces, chrome, tyres, chain saws, rust, braais, industrial equipment and engines.</li></ul>													
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Water-based</li><li>• Non-flammable</li><li>• Non-abrasive</li><li>• No phosphate or chlorine</li><li>• Biodegradable</li><li>• Industrial strength</li></ul>													
<b>Product Information</b>	Appearance	Clear liquid												
	Colours	Umber												
	Flash Point	Non flammable												
	Boiling point	100.2 °C												
	pH	12.5 -13.5												
	VOC Content	111 g/l												
	Density	1.01 g/ml												
	Viscosity	17 Seconds (Ford 4 Cup)												
	Shelf Life	24 months												
<b>Application Details</b>	Mixing	The product may be diluted as recommended. Stir product before application.												
		<table border="1"><thead><tr><th>Recommended dilution ratio for :</th><th>Degreaser : Water</th></tr></thead><tbody><tr><td>General purpose degreasing</td><td>1:3</td></tr><tr><td>Shop walls, lockers, stove tops, equipment</td><td>1:2</td></tr><tr><td>Tools, overspray, lawn mowers, fireplace/soot:</td><td>1:2</td></tr><tr><td>Chrome, tyres, chainsaws, tar, rust, braais:</td><td>1:2</td></tr><tr><td>Engine parts, industrial equipment:</td><td>Do not dilute</td></tr></tbody></table>	Recommended dilution ratio for :	Degreaser : Water	General purpose degreasing	1:3	Shop walls, lockers, stove tops, equipment	1:2	Tools, overspray, lawn mowers, fireplace/soot:	1:2	Chrome, tyres, chainsaws, tar, rust, braais:	1:2	Engine parts, industrial equipment:	Do not dilute
Recommended dilution ratio for :	Degreaser : Water													
General purpose degreasing	1:3													
Shop walls, lockers, stove tops, equipment	1:2													
Tools, overspray, lawn mowers, fireplace/soot:	1:2													
Chrome, tyres, chainsaws, tar, rust, braais:	1:2													
Engine parts, industrial equipment:	Do not dilute													
	Method	Brush, hand sprayer, pump-style garden sprayer or chemical applicator.												
	Substrate	All substrate types.												
<b>Storage and Packaging</b>	Store away from direct sun, heat and severe cold. Packaging: 1ℓ and 3ℓ													



# REMOVAL GREASE & GRIME REMOVER

PRODUCT CODE: RCS 60

TECHNICAL DATA SHEET NO: D-8-C

---

<b>Application</b>	<ul style="list-style-type: none"><li>• Dilute product in a plastic bucket according to the dilution ratio described in application details.</li><li>• Coat all surfaces with <b>REMOVAL GREASE &amp; GRIME REMOVER</b> using a brush, mop, stainless steel or plastic sprayer.</li><li>• Wait 1-5 minutes for product to penetrate dirt, grease and grime. Agitate or scrub if necessary.</li><li>• Allow product to be in contact with the surface longer (up to 20 minutes) if you have difficult areas/parts to clean.</li><li>• Rinse area thoroughly with water using a cloth, mop or hose.</li><li>• Wash vertical surfaces from top to bottom.</li><li>• Rinse all project surfaces thoroughly with water.</li></ul>
<b>Safety Precautions</b>	<ul style="list-style-type: none"><li>• Always keep remover out of reach of children.</li><li>• Ensure good ventilation during application.</li><li>• Wear protective gloves and goggles while applying.</li><li>• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.</li><li>• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.</li><li>• Harmful if swallowed. Seek medical attention and do not induce vomiting.</li><li>• Store in a cool, dry place away from heat and sparks.</li><li>• Refer to Material Safety Data Sheet for complete information.</li></ul>

---

**DISCLAIMER:**

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

**PLASCON SOUTH AFRICA (PTY) LIMITED**

**CAPE TOWN:**

P. O. Box 42  
Eppindust 7475  
Tel: (021) 505-2400  
Fax: (021) 534-3791

**DURBAN:**

Private Bag X16  
Mobeni 4060  
Tel: (031) 451-3200  
Fax: (031) 451-3411

**GAUTENG:**

P.O. Box 4010  
Luipaardsvlei 1743  
Tel: (011) 951-4500  
Fax: (011) 955-2841

**PORT ELIZABETH:**

P.O.Box 1594  
Port Elizabeth 6000  
Tel: (041) 401-1400  
Fax: (041) 453-4606