



# REMOVAL SIMPLE WASH

PRODUCT CODE: RWS 80

TECHNICAL DATA SHEET NO: D-17-D

DATE: FEBRUARY 2011

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

<b>Product Description</b>	A water-based surface cleaner, brightener and restorer.									
<b>Intended Uses</b>	Ideal for removing mould, tannin, mildew, grime, water and rust stains. Brightens up wood by removing chalky oxidised surface build-up.									
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Water-based</li><li>• Biodegradable</li><li>• Easy to use</li><li>• Contains no bleach</li><li>• Water rinse clean up</li><li>• Safe on treated lumber and exotic wood</li></ul>									
<b>Product Information</b>	Appearance	Clear liquid								
	Colours	Green								
	Flash Point	N/A								
	Boiling point	99.3 °C								
	pH	0.5 - 1								
	VOC Content	0 g/l								
	Density	105 g/ml								
	Viscosity	48 Seconds (Ford 4 Cup)								
	Shelf Life	24 months								
<b>Application Details</b>	Mixing	The product may be diluted as recommended.								
		<table border="1"><thead><tr><th>Recommended dilution ratio for:</th><th>Simple Wash : Water</th></tr></thead><tbody><tr><td>Etching concrete, heavy duty cleaning, tough rust stains</td><td>1:1</td></tr><tr><td>General purpose cleaning, wood brightening</td><td>1:2</td></tr><tr><td>Light duty cleaning and wood brightening</td><td>1:2</td></tr></tbody></table>	Recommended dilution ratio for:	Simple Wash : Water	Etching concrete, heavy duty cleaning, tough rust stains	1:1	General purpose cleaning, wood brightening	1:2	Light duty cleaning and wood brightening	1:2
Recommended dilution ratio for:	Simple Wash : Water									
Etching concrete, heavy duty cleaning, tough rust stains	1:1									
General purpose cleaning, wood brightening	1:2									
Light duty cleaning and wood brightening	1:2									
	Substrate	Outdoor weathered wood surfaces and pressure treated lumber, plastic, concrete and fibreglass.								
	Method	Brush or a small hand pump, weed sprayer or conventional spray equipment capable of producing a fine atomised spray.								
<b>Storage &amp; Packaging</b>	Store away from direct sun, heat and severe cold. Do not store or use in metal pails. Packaging: 1ℓ and 3ℓ									



# REMOVAL SIMPLE WASH

PRODUCT CODE: RWS 80

TECHNICAL DATA SHEET NO: D-17-D

<b>Application</b>	<ul style="list-style-type: none"><li>• Dilute <b>REMOVAL SIMPLE WASH</b> in a plastic bucket according to dilutions described in application details.</li><li>• Wash all surfaces from the top down using a synthetic brush, stainless steel or plastic sprayer, or mop and scrub where required.</li><li>• Wait 5-20 minutes for product to penetrate dirt, grime, mildew, stains or until desired wood brightness is obtained. Agitate or scrub if necessary.</li><li>• Allow product to be in contact with the surface longer if you have difficult areas/parts to clean.</li><li>• A second application or weaker dilution may be required for cedar or redwood.</li><li>• Rinse wood thoroughly in direction of grain with water using a cloth, mop or garden hose or 500 to 1200 psi pressure washer. Heavily weathered wood surfaces may look fibrous after rinsing the remover. Immediately brushing along the wood grain helps remove the loose fibre.</li></ul>
<b>Caution</b>	<ul style="list-style-type: none"><li>• Product may corrode bare metal.</li><li>• Contains weak acids, alkylbenzene sulfonic acid (CAS # 68584-22-5) and phosphoric acid (CAS # 7664-38-2).</li></ul>
<b>Safety Precautions</b>	<ul style="list-style-type: none"><li>• Always keep remover out of reach of children.</li><li>• Wear protective gloves and goggles while applying.</li><li>• Ensure good ventilation during application.</li><li>• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.</li><li>• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.</li><li>• Harmful if swallowed. Seek medical attention and do not induce vomiting.</li><li>• Store in a cool, dry place away from heat and sparks.</li><li>• Refer to Material Safety Data Sheet for complete information.</li></ul>

## DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

**NB:** Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

**NB: TO ORDER:** Quote product name, product code number, packaging and colour.

## PLASCON SOUTH AFRICA (PTY) LIMITED

### CAPE TOWN:

P. O. Box 42  
Eppindust 7475  
Tel: (021) 505-2400  
Fax: (021) 534-3791

### DURBAN:

Private Bag X16  
Mobeni 4060  
Tel: (031) 451-3200  
Fax: (031) 451-3411

### GAUTENG:

P.O. Box 4010  
Luipaardsvlei 1743  
Tel: (011) 951-4500  
Fax: (011) 955-2841

### PORT ELIZABETH:

P. O. Box 1594  
Port Elizabeth 6000  
Tel: (041) 401-1400  
Fax: (041) 453-4606