



REMOVALL WEATHERED WOOD RESTORER

PRODUCT CODE: RWW 20

TECHNICAL DATA SHEET NO: D-18-C

DATE: FEBRUARY 2011

THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product Description	A water-based weathered wood restorer.	
Intended Uses	<ul style="list-style-type: none">• Ideal for removing grey wood fibre, mould, mildew and water stains.• Rejuvenates wood by removing deteriorated fibres.	
Features & Benefits	<ul style="list-style-type: none">• Water-based• Biodegradable• Easy to use• Contains no bleach• Water rinse clean-up• Safe on treated lumber and exotic wood	
Product Information	Appearance	Clear liquid
	Colours	Blue
	Flash Point	N/A
	Boiling point	99.9 °C
	pH	12.5 - 13.5
	VOC Content	0 g/l
	Density	1.03 g/ml
	Viscosity	12 S (F4C)
	Shelf life	24 months
Application Details	Mixing	Stir product before application. The product may be slightly diluted for lightly greyed wood, otherwise use it undiluted. Mix only in a plastic bucket do not use a metal container.
	Substrate	Outdoor weathered wood surfaces and pressure treated lumber. Product may harm bare metal or painted surfaces.
	Method	Brush or small hand pump, weed sprayer or conventional spray equipment capable of producing a fine atomised spray.
Storage & Packaging	Store away from direct sun, heat and severe cold. Packaging: 1 l, 3 l and 10 l	



REMOVAL WEATHERED WOOD RESTORER

PRODUCT CODE: RWW 20

TECHNICAL DATA SHEET NO: D-18-C

Application	<ul style="list-style-type: none">• Apply liberally with a garden sprayer or Hamilton's synthetic brush.• Saturate wood surface with REMOVAL WEATHERED WOOD RESTORER, then wait 5 minutes for product to penetrate wood.• Allow product to be in contact with the surface longer if you have difficult areas/parts to clean.• Scrub lightly in direction of grain with a stiff synthetic brush while rinsing with water.• Rinse wood thoroughly with water in the direction of grain using a cloth, mop, garden hose or 500 to 1200 psi pressure washer. Heavily weathered wood surfaces may look fibrous after rinsing the remover. Immediately brushing along the wood grain helps remove the loose fibre.• To brighten up the restored wood use REMOVAL SIMPLE WASH.• Allow to dry before overcoating.
Caution	<ul style="list-style-type: none">• Mix only in a plastic bucket or container; do not use a metal bucket/container.• Contains less than 0,5% sodium hydroxide.(CAS# 1310-73-2)
Safety Precautions	<ul style="list-style-type: none">• Always keep remover out of reach of children.• Wear protective gloves and goggles while applying.• Ensure good ventilation during application.• If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner.• Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention.• Harmful if swallowed. Seek medical attention and do not induce vomiting.• Store in a cool, dry place away from heat and sparks.• Refer to Material Safety Data Sheet for complete information.

DISCLAIMER:

The recommendations contained herein are given in good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS).It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P.O. Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

GAUTENG:

P.O. Box 4010
Luipaardsvlei 1743
Tel: (011) 951-4500
Fax: (011) 955-2841

PORT ELIZABETH:

P. O. Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4606